



## MINI MARVEL

### SPECIAL FEATURES

- Self-priming pump, does not require any footvalve.
- All gunmetal body, to deliver rust free, pure water.
- High tensile bronze, wear resistant impeller, for long trouble free service.
- Totally enclosed, forced draught, fan cooled motor.
- Compact design, and handy size, for perfect portability.
- Suitable for operation on A.C., single phase, domestic connection.
- High efficiency, low power consumption.
- Stainless steel shaft.

### MOTOR

- Totally enclosed, fan cooled
- Horse Power : 0.37 kw/0.5 HP
- Phase : Single phase, 220/240 volts
- Speed : 2800 r.p.m.
- Full load Current : 2.8 amps
- Insulation : 'B' class
- Permanent split, capacitor type
- No centrifugal switch
- Thermal protected


### PUMP

- Self-priming type
- Suction : 25 mm/1"
- Delivery : 25 mm/1"
- Suction lift : 6.5 mtrs/21 ft
- Design : Centrifugal Regenerative
- Impeller ; High tensile bronze
- Pump body : All gun metal/S.S.
- Gland : mechanical seal, carbon-ceramic



### PERFORMANCE

PUMP	POWER kW /HP	OUTPUT IN LPM	TOTAL HEAD IN mtrs.				
			5	10	15	20	30
MINI MARVEL	0.37 / 0.5		38	33	27	22	13



**CHARACTERISTICS :** Unlike normal centrifugal pumps, the power requirement of this type of pump increases with increase in back pressure. The pump should never be operated for long periods against closed valve.